

SC0928E/SC1328E ELECTRIC SCISSOR LIFTS

PRODUCT HIGHLIGHTS



Reduced maintenance costs

- Lower cost of ownership with highly versatile parts and components
- Rapid, convenient transportation with forklift slots and lifting point
- Drawer-door design for easy maintenance



Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions
- Folding guardrails for easy transport



Reliable performance

- Rear-wheel drive, powerful climbing performance
- Small turning radius, flexible operation
- Pothole protection system as standard



Standard configuration

Proportional controls	Self-lock gate on platform	Unidirectional platform extension
Drivable at full height	Non-Marking Tires	DC motor drive
Automatic Braking System	Emergency Descent System	Emergency stop in 3 locations
Tubing Explosion-Proof System	Fault diagnosis system	Tilt protection system
All Motion Alarm	Horn	Scissor Maintenance Prop
Fork Lift Pockets	Charging Protection System	Flashing beacon
Foldable Guard Rails	Automatic pothole protection	Overload sensor

Optional configuration

AC power on the platform	Platform working lights	Air pipe to the platform
--------------------------	-------------------------	--------------------------

SC0928E/SC1328E ELECTRIC SCISSOR LIFTS

Dimensions	SC0928E (Indoors)	SC1328E (Indoors)
Maximum Working Height (A)	15ft 6in	18ft 9in
Maximum Platform Height (B)	9ft 6in	12ft 9in
Overall Length (C)	4ft 8in	4ft 9in
Overall Width (D)	2ft 6in	2ft 6in
Overall Height (Rails up) (E)	6ft 8in	6ft 11in
Overall Height(Rails down)	5ft 4in	5ft 7in
Platform Dimensions (Length/Width) (H) (F)	51x28in	51x28 in
Maximum horizontal extension (G)	2ft	2ft
Minimum Ground Clearance (Stowed)	2.4in	2.4in
Minimum Ground Clearance (Raised)	0.6in	0.6in
Wheel Base	3ft 5in	3ft 5in
Performance		
Platform Allowable Occupants (Indoors)	2	2
S.W.L.	530lbs	530lbs
S.W.L. On Extension	220lbs	220lbs
Travel Speed (Stowed)	➤2.5 mph	➤2.5mph
Travel Speed (Raised)	➤0.3 mph	➤0.3mph
Up/Down Time	22/20sec	25/27sec
Maximum Gradeability	25%	25%
Minimum Turning Radius	5ft 1in	5ft 1in
Maximum Working Slope	1.5°/3°	1.5°/3°
Tire	Φ9x3in	Φ9x3in
Power		
Batteries	24V80Ah/3HR	24V80Ah/3HR
Integrated Charger	24V/15A	24V/15A
Drive Mode	Electric motor, back-wheel	Electric motor,back-wheel
Lifting Motor	24V DC/1.3kw	24V DC/1.3kw
Drive Motor	2x24V DC/0.45kw	2x24V DC/0.45kw
Weight		
Overall Weight	1940lbs	1970lbs

We reserve the right to make specification changes without notification.

The above represents the current specifications at time of publication. 04.2025

